

RESOLUTION NO. 07-0037

**A RESOLUTION OF
THE PLANNING COMMISSION OF THE CITY OF EL PASO DE ROBLES
APPROVING PLANNED DEVELOPMENT 06-009 AND TENTATIVE TRACT MAP 2889
FOR PROPERTY LOCATED AT 745 PARK STREET, APN 009-201-005
APPLICANT – CHRIS MADSON**

WHEREAS, PD 06-009 and TTM 2889 has been filed by Chris Madson; and

WHEREAS, PD 06-009 and TTM 2889 is an application to develop a mixed-use project with up to 11,178 s.f., and includes 2,600 s.f. restaurant, 1,280 s.f. office, and 6 residences; and

WHEREAS, the project is consistent with the General Plan land use designation Community Commercial / Mixed Use Overlay (CC/M-U) and the Zoning district which is Highway Commercial-Planned Development / Mixed Use Overlay (C2-PD/M-U); and

WHEREAS, the proposed project is consistent with and supports implementation of the *2006 Paso Robles Economic Strategy* since it proposes an efficient use of land and infrastructure, and is proposed as a mixed use, compact, pedestrian oriented development near transit facilities; and

WHEREAS, the applicant requested a Joint Use Parking Exception to allow shared use of four parking spaces between daytime and evening land uses; and

WHEREAS, the Planning Commission held a duly noticed public hearing on March 27, 2007 on this project to accept public testimony on the Planned Development application PD 06-009 and TTM 2889; and

WHEREAS, pursuant to the Statutes and Guidelines of the California Environmental Quality Act (CEQA), and the City's Procedures for Implementing CEQA, this project is Categorical Exempt (Class 32/Infill) from environmental review; and

WHEREAS, based upon the facts and analysis presented in the staff report and the attachments thereto, the public testimony received, and subject to the Conditions of Approval listed below, the Planning Commission makes the following findings:

1. The design and intensity/density of the proposed Planned Development is consistent C2-PD/MU zoning district and the adopted codes, policies, standards and plans of the City, specifically the Zoning Ordinance and General Plan; and
2. The proposed development plan will not be detrimental to the health, safety, morals, comfort, convenience and general welfare of the residents and or businesses in the surrounding area, or be injurious or detrimental to property and improvements in the neighborhood or to the general welfare of the City since the project will improve the existing quality of development on the site and neighborhood; and
3. The proposed development plan accommodates the aesthetic quality of the City as a whole, since the proposal provides for a well designed building with high quality materials, and complies with the Mixed Use and Downtown Design Guidelines; and

4. The proposed development plan is compatible with, and is not detrimental to, surrounding land uses and improvements, provides an appropriate visual appearance, and contributes to the mitigation of any environmental and social impacts; and
5. The proposed development plan is compatible with existing scenic and environmental resources such as hillsides, oak trees, vistas, etc.; and
6. The proposed development plan contributes to the orderly development of the City as a whole.
7. The proposed tentative tract map is consistent with the adopted General Plan for the City of El Paso de Robles; and
8. The site is physically suitable for the type of development proposed; and
9. The site is physically suitable for the proposed density of development; and
10. The design of the land division is not likely to cause substantial environmental damage or substantially and unavoidably injure fish or wildlife or their habitat; and
11. The land division proposed is not likely to cause serious public health problems; and
12. The design of the land division will not conflict with easements acquired by the public at large, for access through or use of, property within the proposed subdivision; and
13. The fulfillment of the requirements listed in the Conditions below is a necessary prerequisite to the orderly development of the site and surrounding area.
14. The hours of use for commercial and residential land uses occupy similar hours and do not meet the intent of the City's Joint Use Parking Regulations.

NOW, THEREFORE, BE IT RESOLVED, that the Planning Commission of the City of El Paso de Robles does hereby approve Planned Development 06-009, Tentative Tract Map 2889, and denies the Joint Use Parking Exception subject to the following conditions:

STANDARD CONDITIONS:

1. This project shall comply with the checked standard Conditions of Approval, attached hereto as Exhibit "A" and incorporated herein by reference.

SITE SPECIFIC CONDITIONS:

NOTE: In the event of conflict or duplication between standard and site-specific conditions, the site-specific condition shall supersede the standard condition.

- 2. The project shall be constructed in substantial conformance with the Conditions of Approval established by this Resolution and it shall be constructed in substantial conformance with the following Exhibits:

EXHIBIT	DESCRIPTION
A	Standard Conditions of Approval
B	Site Plan
C	Exterior Elevations

- 3. This PD 06-009 and TTM 2889 is an application to develop a mixed-use project with up to 11,178 s.f., and includes 2,600 s.f. restaurant, 1,280 s.f. office, and 6 residences as permitted in the Zoning Ordinance on the project site.
- 4. The project shall be designed and constructed to be in substantial conformance with the site plan and elevations approved with this resolution.
- 5. Approval of this project is valid for a period of two (2) years from date of approval. Unless permits have been issued and site work has begun, the approval of PD 06-009 and TPM 2889 shall expire on March 27, 2009. The Planning Commission may extend this expiration date for an additional three (3) years if a time extension application has been filed with the City along with the fees before the expiration date.
- 6. Prior to issuance of certificates of use and occupancy, the property-owner or authorized agent is required to pay the City's Development Impact Fees.
- 7. No underground or aboveground storage of hazardous materials shall be allowed on-site without first obtaining City approval.
- 8. No storage of trash cans or recycling bins shall be permitted within the public right-of-way.
- 9. Temporary construction noise levels in excess of 60 decibels shall be restricted to the daylight hours of 7am to 6pm. Noise levels shall be measured or monitored from site boundaries or the nearest adjoining residential use to determine compliance.
- 10. Use and operation of the project and its appurtenances shall be conducted in compliance with the City's General Performance Standards for all uses (Section 21.21.040 of Chapter 21.21 Performance Standards of the City's Zoning Ordinance).
- 11. Prior to occupancy, the applicant shall relocate overhead utility lines adjacent to the property underground (with the exception of 70kv transmission lines).
- 12. Prior to grading permit, the applicant shall provide plans for the treatment of storm water leaving the site.
- 13. The applicant shall provide 16 on-site parking spaces and shall be required to pay parking in-lieu fees for four parking spaces.
- 14. The applicant shall take the steps necessary to annex to or form a City Community Facilities District (CFD) in order to provide funding for City services for each new parcel or dwelling unit in the proposed

development. The agreement to form or annex to a CFD shall be in a manner to be approved by the City Attorney. Participation in a City CFD for services is intended to fully mitigate the incremental impact of new residential development on City services.

In order to insure that there is adequate and consistent funding to provide for City services in a manner reflective of adopted General Plan standards, it is necessary to provide a “fall back” funding mechanism in case, for any reason, it is not possible to annex to or form a CFD that would fully mitigate the incremental fiscal impacts on City services. A fall back funding mechanism is also needed if a CFD is formed and for whatever reason the CFD is invalidated or otherwise is incapable of meeting its intended purpose of fully mitigating the impacts of new residential development on City services.

In order to insure that there is an alternative form of fiscal mitigation, prior to final approval of any project creating additional residential lots or dwelling units, the property owner shall agree, in a manner subject to approval by the City Attorney, to provide for alternative means of fiscal mitigation. The alternative means of fiscal mitigation could include, but would not be limited to, equivalent services being provided by a Homeowners Association, a perpetual endowment to cover the incremental costs of City services (including a CPI adjustment), a City road maintenance assessment district, or a combination of such tools to insure full fiscal mitigation of impacts to City services.

15. The project shall be in compliance the following recommendations of the San Luis Obispo County Air Pollution Control District so as to minimize creation of fugitive dust and other emission resulting from use of construction equipment as follows:

CONSTRUCTION PHASE MITIGATION:

Dust Control Measures

Construction activities can generate fugitive dust, which could be a nuisance to local residents and businesses in close proximity to the proposed construction site. Dust complaints could result in a violation of the District’s 402 “Nuisance” Rule. Due to this project’s proximity to neighboring commercial uses the APCD conditions this project to comply with all applicable air quality regulations pertaining to the control of fugitive dust (PM10) as contained in section 6.5 of the Air Quality Handbook. **All site grading and demolition plans noted shall list the following regulations:**

- a. Reduce the amount of the disturbed area where possible.
- b. Use of water trucks or sprinkler systems in sufficient quantities to prevent airborne dust from leaving the site. Increased watering frequency would be required whenever wind speeds exceed 15 mph. Reclaimed (nonpotable) water should be used whenever possible.
- c. All dirt stock pile areas should be sprayed daily as needed.
- d. Permanent dust control measures identified in the approved project revegetation and landscape plans should be implemented as soon as possible following completion of any soil disturbing activities.
- e. Exposed ground areas that are planned to be reworked at dates greater than one month after initial grading should be sown with a fast germinating native grass seed and watered until vegetation is established.
- f. All disturbed soil areas not subject to revegetation should be stabilized using approved chemical soil binders, jute netting, or other methods approved in advance by the APCD.
- g. All roadways, driveways, sidewalks, etc. to be paved should be completed as soon as possible. In addition, building pads should be laid as soon as possible after grading unless seeding or soil binders are used.
- h. Vehicle speed for all construction vehicles shall not exceed 15 mph on any unpaved surface at the construction site.
- i. All trucks hauling dirt, sand, soil, or other loose materials are to be covered or should maintain at least two feet of freeboard (minimum vertical distance between top of load and top of trailer) in accordance with CVC Section 23114.
- j. Install wheel washers where vehicles enter and exit unpaved roads onto streets, or wash off trucks

- and equipment leaving the site.
- k. Sweep streets at the end of each day if visible soil material is carried onto adjacent paved roads. Water sweepers with reclaimed water should be used where feasible.

All PM10 mitigation measures required should be shown on grading and building plans. In addition, the contractor or builder should designate a person or persons to monitor the dust control program and to order increased watering, as necessary, to prevent transport of dust offsite. Their duties shall include holidays and weekend periods when work may not be in progress. **The name and telephone number of such persons shall be provided to the APCD prior to land use clearance for map recordation and finished grading of the area.**
Naturally Occurring Asbestos

The project site is located in a candidate area for Naturally Occurring Asbestos (NOA), which has been identified as a toxic air contaminant by the California Air Resources Board (ARB). Under the ARB Air Toxics Control Measure (ATCM) for Construction, Grading, Quarrying, and Surface Mining Operations, **prior to any grading activities at the site, the project proponent shall ensure that a geologic evaluation is conducted to determine if NOA is present within the area that will be disturbed.** If NOA is not present, an exemption request must be filed with the District (see Attachment 1). If NOA is found at the site the applicant must comply with all requirements outlined in the Asbestos ATCM. This may include development of an Asbestos Dust Mitigation Plan and an Asbestos Health and Safety Program for approval by the APCD. Please refer to the APCD web page at <http://www.slocleanair.org/business/asbestos.asp> for more information or contact Karen Brooks of our Enforcement Division at 781-5912.

Permits

Based on the information provided, we are unsure of the types of equipment that may be present at the site. Portable equipment used during construction activities may require California statewide portable equipment registration (issued by the California Air Resources Board) or a District permit. Operational sources, such as back up generators, may also require APCD permits. **To minimize potential delays, prior to the start of the project, please contact David Dixon of the District's Engineering Division at (805) 781-5912 for specific information regarding permitting requirements.**

OPERATIONAL PHASE MITIGATION:

The APCD staff considered the operational impact of this commercial development by running the URBEMIS 2002 computer model, a tool for estimating vehicle travel, fuel use and the resulting emissions related to this project's land uses. This indicated that operational phase impacts will not likely be more than the APCD's CEQA Tier I significance threshold value of 10 lbs/day for nitrogen oxides (NOx), Reactive Organic Gases (ROG) and Particulate Matter (PM10). However, the following measures are recommended for this project.

Standard Mitigation Measures (Include all standard mitigation measures below)

- Provide on-site bicycle parking. One bicycle parking space for every 10 car parking spaces is considered appropriate.
- Increase the building energy efficiency rating by 10% above what is required by Title 24 requirements. This can be accomplished in a number of ways (increasing attic, wall, or floor insulation, installing double pane windows, using efficient interior lighting, etc.).

Energy Efficiency Measures

- Use roof material with a solar reflectance value meeting the EPA/DOE Energy Star® rating to reduce summer cooling needs.
- Install door sweeps or weather stripping if more energy efficient doors and windows are not available.

OPERATIONAL PERMIT REQUIREMENTS & MIXED USE INCOMPATIBILITY:

Based on the information provided, we are unsure of the types of equipment that may be present at the site. Operational source may require APCD permits. The following list is provided as a guide to equipment and operations that may have permitting requirements, but should not be viewed as exclusive. For a more detailed listing, refer to page A-5 in the District's CEQA Handbook.

- Portable generators and equipment with engines that are 50 hp or greater;
- Electrical generation plants or the use of standby generator;
- Food and beverage preparation (primarily coffee roasters);
- Dry cleaning;
- Boilers; and
- IC Engines.

As individual project move forward it is important to keep in mind that some uses may not be compatible and could result in potential nuisance problems (i.e. odors and/or dust). The following uses could be problematic if residential quarters are included in the same building and could require an APCD permit.

- Nail Salons;
- Dry-cleaners;
- Coffee roasters;
- Furniture refurbishing/refinishing; and
- Any type of spray paint operation.

16. All lighting shall be shielded and downcast to reduce light and glare spillage onto adjacent properties in compliance with City codes.
17. The applicant shall submit a sign program that is in compliance with provisions in the sign ordinance and provides a unified sign design program that compliments and is coordinated with the architectural design and materials used in the buildings.
18. The outdoor area under the oak tree canopy shall be installed with grasscrete and paver blocks as shown on the site plan. This area shall not be used for vehicle parking or storage of materials.
19. All tree protection measures recommended by the project arborist in compliance with the City's Oak Tree Protection Ordinance shall be implemented as follows:
 - a. Limit grading for the driveway area to removal of asphalt only. The project engineer should be aware of this mitigation prior to setting final building grades. Any deep grading for fill sand and concrete may damage the roots. There are two options for the driveway. The first is concrete on compacted, crushed gravel (geogrid) with curbing (through the concrete) four feet on center within the drip line. The second is porous pavers. Both these options shall be constructed on top of the existing grade. The project owner should contact the owner of the tree to discuss pruning some weight off the tree over the driveway area. Utilities shall be routed outside of the CRZ with any deviation monitored by the project arborist.

All other general oak tree protection measures recommended by the project Arborist shall apply, as follows:

- b. It is the responsibility of the **owner or project manager** to provide a copy of this tree protection plan to any and all contractors and subcontractors that work within the critical root zone of any native tree and confirm they are trained in maintaining fencing, protecting root zones and conforming to all tree protection goals. It is highly recommended that each contractor sign and acknowledge this tree protection plan.
- c. Any future changes (within the critical root zone) in the project will need Project Arborist review and implementation of potential mitigation measures before any said changes can proceed.
- d. **Fencing:** The proposed fencing shall be shown in orange ink on the grading plan. It must be a minimum of 4' high chain link, snow or safety fence staked (with t posts 8 feet on center) at the edge of the critical root zone or line of encroachment for each tree or group of trees. The fence shall be up before any construction or earth moving begins. The owner shall be responsible for maintaining an erect fence throughout the construction period. The arborist(s), upon notification, will inspect the fence placement once it is erected. After this time, fencing shall not be moved without arborist inspection/approval. If the orange plastic fencing is used, a minimum of four zip ties shall be used on each stake to secure the fence. All efforts shall be made to maximize the distance from each saved tree. Weather proof signs shall be permanently posted on the fences every 50 feet, with the following information:

Tree Protection Zone
 No personnel, equipment,
 materials, and vehicles are
 allowed
 Do not remove or re-position
 this fence without calling:
 A & T Arborists
 434-0131

- e. **Soil Aeration Methods:** Soils within the critical root zone that have been compacted by heavy equipment and/or construction activities must be returned to their original state before all work is completed. Methods include water jetting, adding organic matter, and boring small holes with an auger (18" deep, 2-3' apart with a 2-4" auger) and the application of moderate amounts of nitrogen fertilizer. The arborist(s) shall advise.
- f. **Chip Mulch:** All areas within the critical root zone of the trees that can be fenced shall receive a 4-6" layer of chip mulch to retain moisture, soil structure and reduce the effects of soil compaction.
- g. **Trenching Within Critical Root Zone:** All trenching within the critical root zone of native trees shall be **hand dug**. All major roots shall be avoided whenever possible. All exposed roots larger than 1" in diameter shall be clean cut with sharp pruning tools and not left ragged. A **Mandatory** meeting between the arborists and grading contractor(s) must take place prior to work start.
- h. **Grading Within The Critical Root Zone:** Grading should not encroach within the critical root zone unless authorized. Grading should not disrupt the normal drainage pattern around the trees. Fills should not create a ponding condition and excavations should not leave the tree on a rapidly draining mound.

- i. **Exposed Roots:** Any exposed roots shall be re-covered the same day they were exposed. If they cannot, they must be covered with burlap or another suitable material and wetted down 2x per day until re-buried.
- j. **Equipment Operation:** Vehicles and all heavy equipment shall not be driven under the trees, as this will contribute to soil compaction. Also there is to be no parking of equipment or personal vehicles in these areas. All areas behind fencing are off limits unless pre-approved by the arborist.
- k. **Existing Surfaces:** The existing ground surface within the critical root zone of all oak trees shall not be cut, filled, compacted or pared, unless shown on the grading plans **and** approved by the arborist.
- l. **Construction Materials and Waste:** No liquid or solid construction waste shall be dumped on the ground within the critical root zone of any native tree. The critical root zone areas are not for storage of materials either.
- m. **Arborist Monitoring:** An arborist shall be present for selected activities (trees identified on spreadsheet and items bulleted below). The monitoring does not necessarily have to be continuous but observational at times during these activities. It is the responsibility of the **owner(s) or their designee** to inform us prior to these events so we can make arrangements to be present. All monitoring will be documented on the field report form which will be forwarded to the project manager and the City of Paso Robles Planning Department.
- n. ● pre-construction fence placement inspection
- o. ● all grading and trenching identified on the spreadsheet
- p. ● any other encroachment the arborist feels necessary
- q. **Pre-Construction Meeting:** An on-site pre-construction meeting with the Arborist(s), Owner(s), Planning Staff, and the earth moving team shall be required for this project. Prior to final occupancy, a letter from the arborist(s) shall be required verifying the health/condition of all impacted trees and providing any recommendations for any additional mitigation. The letter shall verify that the arborist(s) were on site for all grading and/or trenching activity that encroached into the critical root zone of the selected native trees, and that all work done in these areas was completed to the standards set forth above.
- r. **Pruning :** Class 1 pruning has emphasis on aesthetics, removal of dead, dying, decaying weak branches and selective thinning to lesson wind resistance. Class 2 pruning is recommended where aesthetic conditions are secondary to structural integrity and tree health concerns. It shall consist of removal of dead, dying, decaying, interfering, obstructing and weak branches as well as selective thinning to lesson wind resistance. Class 4 pruning includes-Crown reduction pruning shall consist of reduction of tops, sides or individual limbs. A trained arborist shall perform all pruning. No pruning shall take more than 25% of the live crown of any native tree. Any trees that may need pruning for road/home clearance shall be pruned **prior** to any grading activities to avoid any branch tearing.
- s. **Landscape:** All landscape within the critical root zone shall consist of drought tolerant or native varieties. Lawns shall be avoided. All irrigation trenching shall be routed around critical root zones, otherwise above ground drip-irrigation shall be used. It is the owner's

responsibility to notify the landscape contractor regarding this mitigation. For this site it is strongly recommended that drought tolerant native landscape is used with the approval of the arborist. This includes all city sidewalk/greenbelt areas.

- t. **Utility Placement:** All utilities, sewer and storm drains shall be placed down the roads and driveways and when possible outside of the critical root zones. The arborist shall supervise trenching within the critical root zone. **All trenches in these areas shall be exposed by air spade or hand dug with utilities routed under/over** roots larger than 3 inches in diameter.
- u. **Fertilization and Cultural Practices:** As the project moves toward completion, the arborist(s) may suggest either fertilization and/or mycorrhiza applications that will benefit tree health. Mycorrhiza offers several benefits to the host plant, including faster growth, improved nutrition, greater drought resistance, and protection from pathogens.

20. The applicant shall obtain approval from City Council prior to demolition of the existing older home.

ENGINEERING CONDITIONS

- 21. Prior to occupancy, the applicant shall construct curb, gutter, sidewalk and paving on 8th and Park Streets in accordance with plans approved by the City Engineer.
- 22. Prior to occupancy, the applicant shall install a new fire hydrant at the intersection of 8th and Park Streets. The applicant shall extend an 8-inch water main from either Pine Street or Spring Street as needed to provide a source for a fire line connection and for the new fire hydrant.
- 23. Prior to occupancy, the applicant shall relocate all overhead utilities adjacent to the project on Park Street and the alley, underground. A new street light shall be placed on Park Street.
- 24. Low impact drainage devices shall be incorporated into the project design to the extent feasible.

EMERGENCY SERVICES CONDITIONS

- 25. Provide fire sprinkler systems for residential and commercial buildings.
- 26. Provide fire hydrant at the corner of 8th and Park Streets to meet project fire flow demands.
- 27. Provide documentation prior to the start of construction to Emergency Services showing that required fire flows can be provided to meet all project demands.

PASSED AND ADOPTED THIS 27th day of March, 2007 by the following Roll Call Vote:

AYES: Commissioners – Flynn, Johnson, Menath, Steinbeck, Treach, Withers, Holstine
NOES:
ABSENT:
ABSTAIN:

CHAIRMAN MARGARET HOLSTINE

ATTEST:

RON WHISENAND, PLANNING COMMISSION SECRETARY

EXHIBIT A OF RESOLUTION 07-0037

**CITY OF EL PASO DE ROBLES STANDARD DEVELOPMENT CONDITIONS
FOR PLANNED DEVELOPMENTS / CONDITIONAL USE PERMITS**

PROJECT #: PD 06-020

APPROVING BODY: PLANNING COMMISSION

DATE OF APPROVAL: MARCH 27, 2007

APPLICANT: MADSON

LOCATION: 745 PARK STREET

The following conditions that have been checked are standard conditions of approval for the above referenced project. The checked conditions shall be complied with in their entirety before the project can be finalized, unless otherwise specifically indicated. In addition, there may be site specific conditions of approval that apply to this project in the resolution.

COMMUNITY DEVELOPMENT DEPARTMENT - The applicant shall contact the Community Development Department, (805) 237-3970, for compliance with the following conditions:

A. GENERAL CONDITIONS:

- 1. This project approval shall expire on March 27, 2009 (See Planned Development Approval Resolution) unless a time extension request is filed with the Community Development Department prior to expiration.
- 2. The site shall be developed and maintained in accordance with the approved plans and unless specifically provided for through the Planned Development process shall not waive compliance with any sections of the Zoning Code, all other applicable City Ordinances, and applicable Specific Plans.
- 3. Prior to occupancy, all conditions of approval shall be completed to the satisfaction of the City Engineer and Community Developer Director or his designee.
- 4. Any site specific condition imposed by the Planning Commission in approving this project may be modified or eliminated, or new conditions may be added, provided that the Planning Commission shall first conduct a public hearing in the same manner as required for the approval of this project. No such modification shall be made unless the Commission finds that such modification is necessary to protect the

public interest and/or neighboring properties, or, in the case of deletion of an existing condition, that such action is necessary to permit reasonable operation and use for this approval.

- 5. This project is subject to the California Environmental Quality Act (CEQA) which requires the applicant submit a \$25.00 filing fee for the Notice of Determination payable to "County of San Luis Obispo". The fee should be submitted to the Community Development Department within 24 hours of project approval which is then forwarded to the San Luis Obispo County Clerk. Please note that the project may be subject to court challenge unless the required fee is paid.
- 6. The site shall be kept in a neat manner at all times and the landscaping shall be continuously maintained in a healthy and thriving condition.
- 7. All signs shall be subject to review and approval as required by Municipal Code Section 21.19 and shall require a separate application and approval prior to installation of any sign.
- 8. All outdoor storage shall be screened from public view by landscaping and walls or fences per Section 21.21.110 of the Municipal Code.
- 9. All trash enclosures shall be constructed of decorative masonry block compatible with the main buildings. Gates shall be view obscuring and constructed of durable materials such as painted metal or chain link with plastic slatting.
- 10. All existing and/or new ground-mounted appurtenances such as air-conditioning condensers, electrical transformers, backflow devices etc., shall be screened from public view through the use of decorative walls and/or landscaping subject to approval by the Community Development Director or his designee. Details shall be included in the building plans.
- 11. All existing and/or new roof appurtenances such as air-conditioning units, grease hoods, etc. shall be screened from public view. The screening shall be architecturally integrated with the building design and constructed of compatible materials to the satisfaction of the Community Development Director or his designee. Details shall be included in the building plans.
- 12. All existing and/or new lighting shall be shielded so as to be directed downward in such a manner as to not create off-site glare or adversely impact adjacent properties. The style, location and height of the lighting fixtures shall be submitted with the building plans and shall be subject to approval by the Community Development Director or his designee.

- 13. All existing and/or new landscaping shall be installed with automatic irrigation systems.
- 14. All walls/fences and exposed retaining walls shall be constructed of decorative materials which include but are not limited to splitface block, slumpstone, stuccoed block, brick, wood, crib walls or other similar materials as determined by the Development Review Committee, but specifically excluding precision block.
- 15. The following areas shall be placed in the Landscape and Lighting District:

The developer shall install all improvements and landscape areas. City acceptance on behalf of the Landscape and Lighting District shall be subject to the approval of the Public Works Street Department (237-3864).

- 16. All parking lot landscape planters shall have a minimum outside dimension of six feet and shall be separated from parking and driving areas by a six inch high solid concrete curb.
- 17. The following areas shall be permanently maintained by the property owner, Homeowners' Association, or other means acceptable to the City:

- 18. It is the property owner's responsibility to insure that all construction of private property improvements occur on private property. It is the owner's responsibility to identify the property lines and insure compliance by the owner's agents.

B. THE FOLLOWING CONDITIONS SHALL BE COMPLETED PRIOR TO THE ISSUANCE OF BUILDING PERMITS:

- 1. Two sets of the revised Planning Commission approved plans incorporating all Conditions of Approval, standard and site specific, shall be submitted to the Community Development Department prior to the issuance of building permits.

- 2. Prior to the issuance of building permits, the
 - Development Review Committee shall approve the following:
 - Planning Division Staff shall approve the following:
 - a. A detailed site plan indicating the location of all structures, parking layout, outdoor storage areas, walls, fences and trash enclosures;
 - b. A detailed landscape plan;
 - c. Detailed building elevations of all structures indicating materials, colors, and architectural treatments;
 - d. Other: See PD 00-023 Resolution for specific DRC review requirements.
- 3. The applicant shall meet with the City's Crime Prevention Officer prior to the issuance of building permits for recommendations on security measures to be incorporated into the design of the structures to be constructed. The applicant is encouraged to contact the Police Department at (805) 237-6464 prior to plan check submittal.

C. THE FOLLOWING CONDITIONS SHALL BE COMPLETED PRIOR TO OCCUPANCY:

- 1. Occupancy of the facility shall not commence until such time as all Uniform Building Code and Uniform Fire Code regulations have been complied with. Prior to occupancy, plans shall be submitted to the Paso Robles Fire Department and the Building Division to show compliance. The building shall be inspected by the appropriate department prior to occupancy.
- 2. All public or private manufactured slopes located adjacent to public right-of-ways on property in excess of six (6) feet in vertical height and of 2.5:1 or greater slope shall be irrigated and landscaped for erosion control and to soften their appearance as follows: one 15-gallon tree per each 250 square feet of slope area, one 1-gallon or larger size shrub per each 100 square feet of slope area, and appropriate ground cover. Trees and shrubs shall be staggered in clusters to soften and vary the slope plane. Slope planting shall include a permanent irrigation system be installed by the developer prior to occupancy. In lieu of the above planting ratio, the applicant may submit a slope planting plan by a licensed landscape architect or contractor providing adequate landscaping, erosion control and slope retention measures; the slope planting plan is subject to approval by the Development Review Committee. Hydroseeding may be considered on lots of 20,000 square feet or greater.

PUBLIC WORKS DEPARTMENT - The applicant shall contact the Engineering Division, (805) 237-3860, for compliance with the following conditions:

APPLICANT: MADSON PREPARED BY: JF
REPRESENTATIVE: _____ CHECKED BY: _____
PROJECT: PD 06-009 TO PLANNING: _____

All conditions marked are applicable to the above referenced project for the phase indicated.

D. PRIOR TO ANY PLAN CHECK:

1. The applicant shall enter into an Engineering Plan Check and Inspection Services Agreement with the City.

E. PRIOR TO ISSUANCE OF A GRADING PERMIT:

1. Prior to approval of a grading plan, the developer shall apply through the City, to FEMA and receive a Letter of Map Amendment (LOMA) issued from FEMA. The developer's engineer shall provide the required supporting data to justify the application.
2. The proposed structures and grading shall not encroach into the 100-year floodway as specified in Municipal Code Chapter 21.14 "Flood Damage Prevention Regulations".
3. Any existing Oak trees located on the project site shall be protected and preserved as required in City Ordinance No. 553, Municipal Code No. 10.01 "Oak Tree Preservation", unless specifically approved to be removed. An Oak tree inventory shall be prepared listing the Oak trees, their disposition, and the proposed location of any replacement trees required. In the event an Oak tree is designated for removal, an approved Oak Tree Removal Permit must be obtained from the City, prior to removal.
4. A complete grading and drainage plan prepared by a registered civil engineer shall be included with the improvement plans. Drainage calculations shall be submitted, with provisions made for on-site detention/ retention if adequate disposal facilities are not available, as determined by the City Engineer.

- 5. A Preliminary Soils and/or Geology Report shall be prepared by a registered engineer for the property to determine the presence of expansive soils or other soils problems and shall make recommendations regarding grading of the proposed site.

F. PRIOR TO ANY SITE WORK:

- 1. All off-site public improvement plans shall be prepared by a registered civil engineer and shall be submitted to the City Engineer for review and approval. The improvements shall be designed and placed to the Public Works Department Standards and Specifications.
- 2. The applicant shall submit a composite utility plan signed as approved by a representative of each public utility, together with the improvement plans. The composite utility plan shall also be signed by the Water, Fire, Wastewater, and Street Division heads.
- 3. Any grading anticipated during the rainy season (October 15 to April 15) will require the approval of a Construction Zone Drainage and Erosion Control Plan to prevent damage to adjacent property. Appropriateness of areas shall be subject to City Engineer approval.
- 4. Any construction within an existing street shall require a Traffic Control Plan. The plan shall include any necessary detours, flagging, signing, or road closures requested. Said plan shall be prepared and signed by a registered civil or traffic engineer.
- 5. Landscape and irrigation plans for the public right-of-way shall be incorporated into the improvement plans and shall require a signature of approval by the Department of Public Works, Street Superintendent and the Community Development Department.
- 6. The owner shall offer to dedicate and improve the following street(s) to the standard indicated:

<u>Park Street</u>	<u>Westside</u>	<u>A-12</u>
Street Name	City Standard	Standard Drawing No.

- 7. The owner shall offer to dedicate to the City the following easement(s). The location and alignment of the easement(s) shall be to the description and satisfaction of the City Engineer:
 - a. Public Utilities Easement;

- b. Water Line Easement;
- c. Sewer Facilities Easement;
- d. Landscape Easement;
- e. Storm Drain Easement.

G. PRIOR TO ISSUANCE OF A BUILDING PERMIT:

- 1. A final soils report shall be submitted to the City prior to the final inspection and shall certify that all grading was inspected and approved, and that all work has been done in accordance with the plans, preliminary report, and Chapter 70 of the Uniform Building Code.
- 2. The applicants civil and soils engineer shall submit a certification that the rough grading work has been completed in substantial conformance to the approved plans and permit.
- 3. When retaining walls are shown on the grading plan, said walls shall be completed before approval of the rough grade, and prior to issuance of any building permits, unless waived by the Building Official and the City Engineer.
- 4. All property corners shall be staked for construction control, and shall be promptly replaced if destroyed.
- 5. Building permits shall not be issued until the water system has been completed and approved, and a based access road installed sufficient to support the City's fire trucks per Fire Department recommendation.
- 6. The developer shall annex to the City's Landscape and Lighting District for payment of the operating and maintenance costs of the following:
 - a. Street lights;
 - b. Parkway and open space landscaping;
 - c. Wall maintenance in conjunction with landscaping;
 - d. Graffiti abatement;
 - e. Maintenance of open space areas.
- 7. Prior to the issuance of a Building Permit for a building within Flood Insurance Rate Map (FIRM) - in zones A1-A30, AE, AO, AH, A, V1-V30, VE and V - the developer shall provide an Elevation Certificate in accordance with the National Flood Insurance Program. This form must be completed by a land surveyor, engineer or architect licensed in the State of California.
- 8. Prior to the issuance of a Building Permit for a building within Flood Insurance Rate

Map (FIRM) in zones A1-A30, AE, AO, AH, A, V1-V30, VE and V, the developer shall provide a Flood Proofing Certificate in accordance with the National Insurance Program. This form must be completed by a land surveyor, engineer or architect licensed in the State California.

H. PRIOR TO ISSUANCE OF CERTIFICATE OF OCCUPANCY:

- 1. The applicant shall pay any current and outstanding fees for Engineering Plan Checking and Construction Inspection services and any outstanding annexation fees.
- 2. No buildings shall be occupied until all public improvements are completed and approved by the City Engineer, and accepted by the City Council.
- 3. All final property corners and street monuments shall be installed before acceptance of the public improvements.
- 4. All top soil removed shall be stockpiled and evenly distributed over the slopes and lots upon completion of rough grading to support hydroseeding and landscaping. All slope areas shall be protected against erosion by hydroseeding or landscaping.
- 5. The applicant shall install all street names, traffic signs and traffic striping as directed by the City Engineer.
- 6. If the adjoining existing City street is inadequate for the traffic generated by the project, or will be severely damaged by the construction, the applicant shall remove the entire roadway and replace it with a minimum full half-width street plus a 12' wide travel lane and 8' wide graded shoulder adequate to provide for two-way traffic. (A finding of "rough proportionality" has been made in the resolution for this condition).
- 7. If the development includes a phased street construction along the project boundary for future completion by the adjacent property owner, the applicant shall provide a minimum half-width street plus a 12' wide travel lane and 4' wide graded shoulder adequate for two-way traffic. (A finding of "rough proportionality" has been made in the resolution for this condition).
- 8. When the project fronts on an existing street, the applicant shall pave-out from the proposed curb to the edge of pavement if the existing pavement section is adequate, and shall feather the new paving out to the centerline for a smooth transition. If the existing pavement is inadequate, the roadway shall be replaced to centerline and the remaining pavement shall be overlaid. (A finding of "rough proportionality" has been made in the resolution for this condition).

(Adopted by Planning Commission Resolution 94-038)

- 9. Any utility trenching in existing streets shall be overlaid to restore a smooth riding surface as required by the City Engineer. Boring and jacking rather than trenching may be required on newly constructed or heavily traveled City streets.
- 10. The applicant shall install all utilities (sewer, water, gas, electricity, cable TV and telephone) underground (as shown on the composite utility plan). Street lights shall be installed at locations as required by the City Engineer. All existing overhead utilities adjacent to or within the project shall be relocated underground except for electrical lines 77 kilovolts or greater. All utilities shall be extended to the boundaries of the project. All underground construction shall be completed and approved by the public utility companies, and the subgrade shall be scarified and compacted, before paving the streets.
- 11. Prior to paving any street the water and sewer systems shall successfully pass a pressure test. The sewer system shall also be tested by a means of a mandrel and video inspection with a copy of the video tape provided to the City. No paving shall occur until the City has reviewed and viewed the sewer video tape and has determined that the sewerline is acceptable. Any repair costs to the pipeline including trench paving restoration shall be at the developer's expense.
- 12. A blackline clear Mylar (0.4 MIL) copy and a blueline print of as-built improvement plans, signed by the engineer of record, shall be provided to the City Engineer prior to the final inspection. A reduced copy (i.e. 1" = 100') of the composite utility plan shall be provided to update the City's Atlas Map.
- 13. All construction refuse shall be separated (i.e. concrete, asphalt concrete, wood gypsum board, etc.) and removed from the project in accordance with the City's Source Reduction and Recycling Element.

PASO ROBLES FIRE DEPARTMENT - The applicant shall contact the Fire Department, (805) 237-3973, for compliance with the following conditions:

I. GENERAL CONDITIONS

- 1. Fire hydrants shall be installed at intervals as required by the Fire Chief and City Engineer. The maximum spacing for single family residential shall be 500 feet. The maximum spacing for multi-family and commercial/ residential shall be 300 feet. On-site hydrants shall be placed as required by the Fire Chief.
- 2. Building permits shall not be issued until the water system, including hydrants, has been tested and accepted and a based access road installed sufficient to support the City's fire apparatus (HS-20 truck loading). The access road shall be kept clear to a minimum of 24 feet at all times and shall be extended to each lot and shall be maintained to provide all weather driving conditions.
- 3. No buildings shall be occupied until all improvements are completed and accepted by the City for maintenance.
- 4. If the development includes phased street construction, temporary turn-arounds shall be provided for streets that exceed 150 feet in length. The temporary turn around shall meet City requirements as set forth in the Public Works Department Standards and Specifications.
- 5. All open space areas to be dedicated to the City shall be inspected by the Fire Department prior to acceptance. A report shall be submitted recommending action needed for debris, brush and weed removal and tree trimming. The developer shall clean out all debris, dead limbs and trash from areas to be recorded as open space prior to acceptance into a Benefit Maintenance District.
- 6. Any open space included in a private development shall be subject to the approval of a vegetation management plan approved by the Fire Chief.
- 7. Each tract or phase shall provide two sources of water and two points of access unless otherwise determined by the Fire Chief and Public Works Director.
- 8. Provisions shall be made to update the Fire Department Run Book.